







Heavy Duty, Thermoplastic, Power Connectors

Available in Single Position

Our ATHD Series Heavy Duty Power Connectors provide an environmentally-sealed connection system and solution to field splices and terminals in harsh environments. Safety features include an integral latch to prevent inadvertent disconnect and an audible/tactile "click" provides circuit confirmation. Precision machined contact technology maximizes performance and durability while delivering up to 100A of power.

Available in In-Line (Wire-to-Wire), BoardLock™, PanelMate™ and StructurePlus™ options. Also available as cable assemblies in a variety of standard lengths.









Applications: Heavy Duty, Transportation, Marine, Diagnostic, Military, Alternative Energy and Agricultural

Kev Features

- Intermatable with industry standard connectors
- Circular, Thermoplastic Housing
- Integral Latch Prevents Inadvertent Disconnect
- In-line (Wire-to-Wire), BoardLock™ or PanelMate™ Options
- Customized project-specific colors





ATHD Series™ - Specifications (Reference Individual Datasheets)

IP Rating (in mated condition)	IP68 and IP69K (See datasheets)
Max. Current (Amperage)	Up to 100A
Max. Voltage Rating	Up to 1000V
Operating Temperature	-40°C to +125°C
Coupling System	Integrated Latch
Housing Body	Thermoplastic UL94-VO
Contact Types	Stamped & Formed, Machined, Solder
Contact Material	Copper Alloy
Wire Range	4-14AWG (See datasheets)
Sealing Material	Silicone Rubber
Min. Mating Cycles	>100
Flammability Rating	UL94-VO
Fluid Resistance	Gas, oil, mineral oil, acid bath, basic bath
Insulation Resistance	1000 megohms min. of 25°C
RoHS Compliant	ALL materials meet the requirements of the European Directive. (See website for documentation)

Available Modifications

- -BMXX BoardLock™ ATHD/ATFHD Receptacle
- -LOO9 PanelMate™ ATHD Receptacle for inside mounting
- -L013 PanelMate™ ATHD Receptacle for outside mounting
- -OM StructurePlus™ ATHD Overmold Capable
- -E003 Endcap



IP67 rated (Dust tight; 1M of Water for 30 Minutes, in mated condition) IP68 rated (Dust tight; 1M of Water for 24 Hours, in mated condition) IP69K rated (Dust tight; High-Pressure Waterproof, 4 Points (0°, 30°, 60°, 90°), in mated condition)















Standard products. Custom solutions Customer Service +1 800 394 7732 ATHD Series™ - Plugs

INDUSTRIAL@AMPHENOL TRUSTED GLOBALLY

Note: Refer to individual datasheets on www.amphenol-sine.com for full specs, faceviews, keying location and product dimensions.

Image	Part Number	Description	Contact Size	Amp
	ATHD06-1-4S	Single Position, Plug, Pin, ATHD™ Series, Black Body	4	100A
	ATHD06-1-4S-E003	Single Position, Plug, Socket, ATHD™ Series, Endcap, Black Body	4	100A
	ATHD06-1-8S	Single Position, Plug, Socket, ATHD™ Series, Black Body	8	60A
	ATHD06-1-8S-E003	Single Position, Plug, Socket, ATHD™ Series, Endcap, Black Body	8	60A
	ATHD06-1-12S	Single Position, Plug, Socket, ATHD™ Series, Black Body	12	25A
	ATHD06-1-12S-E003	Single Position, Plug, Socket, ATHD™ Series, Endcap, Black Body	12	25A

StructurePlusTM ATHD - Plugs

Note: Refer to individual datasheets on www.amphenol-sine.com for full specs, faceviews, keying location and product dimensions.

(C)	ATHD06-1-4S-OM	Single Position, Plug, Socket, StructurePlus™ ATHD Series, Black body	4	100A
	ATHD06-1-8S-OM	Single Position, Plug, Socket, StructurePlus™ ATHD Series, Black Body	8	60A
	ATHD06-1-12S-OM	Single Position, Plug, Socket, StructurePlus™ ATHD Series, Black	12	25A

ATHD Series™ - Receptacles

Note: Refer to individual datasheets on www.amphenol-sine.com for full specs, faceviews, keying location and product dimensions.

ATHD04-1-4P	Single Position, Receptacle, Pin, ATHD™ Series, Black Body	4	100A
ATHD04-1-4P-E003	Single Position, Receptacle, Pin, ATHD™ Series, Endcap, Black Body	4	100A
ATHD04-1-8P	Single Position, Receptacle, Pin, ATHD™ Series, Black Body	8	60A
ATHD04-1-8P-E003	Single Position, Receptacle, Pin, ATHD™ Series, Endcap, Black Body	8	60A

www.amphenol-sine.com

Image	Part Number	Description	Contact Size	Amp
	ATHD04-1-12P	Single Position, Receptacle, Pin, ATHD™ Series, Black Body	12	25A
	ATHD04-1-12P-E003	Single Position, Receptacle, Pin, ATHD™ Series, Endcap, Black Body	12	25A

BoardLock™ ATHD Series - Receptacles

ATHD04-1-4P-BM11	Single Position, Receptacle, Pin, Size 4, Gold-Plated, BoardLock™ ATHD Series, Keyed A, Self-Threading, No Potting, Black Body	4	10
ATHD04-1-4P-BM12	Single Position, Receptacle, Pin, Size 4, Gold-Plated, BoardLock™ ATHD Series, Keyed A, Self-Threading, Potting, Black Body	4	10
ATHD04-1-4P-BM13	Single Position, Receptacle, Pin, Size 4, Nickel-Plated, BoardLock™ ATHD Series, Keyed A, Self-Threading, No Potting, Black Body	4	10
ATHD04-1-4P-BM14	Single Position, Receptacle, Pin, Size 4, Nickel-Plated, BoardLock™ ATHD Series, Keyed A, Self-Threading, Potting, Black Body	4	1
ATHD04-1-8P-BM11	Single Position, Receptacle, Pin, Size 8, Gold-Plated, BoardLock™ ATHD Series, Self-Threading, No Potting, Black Body	8	6
ATHD04-1-8P-BM12	Single Position, Receptacle, Pin, Size 8, Gold-Plated, BoardLock™ ATHD Series, Self-Threading, Potting, Black Body	8	(
ATHD04-1-8P-BM13	Single Position, Receptacle, Pin, Size 8, Nickel-Plated, BoardLock™ ATHD Series, Self-Threading, No Potting, Black Body	8	
ATHD04-1-8P-BM14	Single Position, Receptacle, Pin, Size 8, Nickel-Plated, BoardLock™ ATHD Series, Self-Threading, Potting, Black Body	8	
ATHD04-1-12P-BM11	Single Position, Receptacle, Pin, Size 12, Gold-Plated, BoardLock™ ATHD Series, Self-Threading, No Potting, Black Body	12	2
ATHD04-1-12P-BM12	Single Position, Receptacle, Pin, Size 12, Gold-Plated, BoardLock™ ATHD Series, Self-Threading, Potting, Black Body	12	2
ATHD04-1-12P-BM13	Single Position, Receptacle, Pin, Size 12, Tin-Plated, BoardLock™ ATHD Series, Self-Threading, No Potting, Black Body	12	2
ATHD04-1-12P-BM14	Single Position, Receptacle, Pin, Size 12, Tin-Plated, BoardLock™ ATHD Series, Self-Threading, Potting, Black Body	12	:

BoardLock™ ATFHD Series - Receptacles

Note: Refer to individual datasheets on www.amphenol-sine.com for full specs, faceviews, keying location and product dimensions.



www.amphenol-sine.com

Image	Part Number	Description	Contact Size	Amp
	ATFHD13-1-4P-BM13	Single Position, Receptacle, Pin, Nickel-Plated, BoardLock™ ATFHD Series, Self-Tapping, Black Body	4	100A

PanelMate™ ATHD Series - Receptacles

Note: Refer to individual datasheets on www.amphenol-sine.com for full specs, faceviews, keying location and product dimensions.

ATHD04-1-4P-L009	Single Position, Receptacle with Inside Mount Sealed Flange, Pin, Size 4, PanelMate™ ATHD Series, Self-Threading, Gasket, Standard Diameter Rear Seal (Red), Black Body	4	100A
ATHD04-1-4P-L013	Single Position, Receptacle with Outside Mount Sealed Flange, Pin, Size 4, PanelMate™ ATHD Series, Self-Threading, Gasket, Standard Diameter Rear Seal (Red), Black Body	4	100A
ATHD04-1-8P-PM05	Single Position, Receptacle with Flange, Pin, Size 8, PanelMate™ ATHD Series, Threaded Insert, Gasket, Standard Diameter Rear Seal (Red), Black Body	8	60A
ATHD04-1-8P-PM11	Single Position, Receptacle with Flange, Pin, Size 8, PanelMate™ ATHD Series, Self-Threading, Gasket, Standard Diameter Rear Seal (Red), Black Body	8	60A
ATHD04-1-12P-PM05	Single Position, Receptacle with Flange, Pin, Size 12, PanelMate™ ATHD Series, Threaded Insert, Gasket, Standard Diameter Rear Seal (Red), Black Body	12	25A
ATHD04-1-12P-PM11	Single Position, Receptacle with Flange, Pin, Size 12, PanelMate™ ATHD Series, Self-Threading, Gasket, Standard Diameter Rear Seal (Red), Black Body	12	25A

ATHD Series™ - Contacts

Note: Refer to individual part number datasheets found at www.amphenol-sine.com or our A Series Contacts Flyer.

© 2020 Amphenol Sine Systems Corporation, 44274 Morley Drive, Clinton Twp MI 48036 USA +1 800 394 7732 www.amphenol-sine.com csr@amphenol-sine.com Every effort has been made to ensure that the information contained in this document is accurate at the time of publication. Specifications or information stated in this document are subject to change without notice.